


ALWAYS PERFORMED WELL



Compressor type Rotary Twin Screw,Single-Stage,Water-cooled

Operational data

Free Air Delivery	m3/min	6.16
	cfm	220
Rated Operating Pressure	bar	8
	psig	116

Engine

Maker/Model		ISUZU JE493YB-01
Type		4 cycle, Inline,Water-cooled, Diesel
Air Intake Way		Naturally Aspirated
Injection System		Mechanical
Emission regulation		N/A
Number of Cylinders		4
Bore	mm	93
Stroke	mm	102
Displacement	l	2.771
Full Load Speed	rpm	3000
Unload Speed	rpm	1800
Power	kw(ps)(bhp)	44.6(60.6) (59.8)
Fuel Consumption	l/h(US gal/h)	11.5(3.04)

Filling capacities

Compressor Oil System	l(US gal)	14.7(3.88)
Diesel Tank	l(US gal)	60(15.85)
Engine Coolant System	l(US gal)	8.1(2.14)
Engine Oil System	l(US gal)	5(1.32)

Dimensions & weight and connections

Box	Length	mm(in)	2170(85)
	Width	mm(in)	1220(48)
	Height	mm(in)	1320(52)
	weight(Dry)	kg(lb)	1150(2533.3)
	weight(Wet)	kg(lb)	1204(2654.4)
Portable	Length	mm(in)	3530(139)
	Width	mm(in)	1743(69)
	Height	mm(in)	1590(63)
	weight(Dry)	kg(lb)	1330(2932)
	weight(Wet)	kg(lb)	1384(3051)
Compressed air outlet		1 x G1 1/2" 3×G3/4"	



* Note: Due to continuous improvements in the products, the technical specifications are subject to change without prior notice.

MDS220S8I Technical Data

Many options for many applications

Compressed Air Quality	Compressor Equipment	Integrated Generator	Engine Accessories	Others
«Built-in aftercooler	«Hose reel	«5KVA «7KVA	«Spark arrestor	«Color
«Built-in microfilter combination	«Remote start / stop	«9KVA «15KVA	«Engine shutdown at overspeed from flammable gases	«Fuel tank capacity
«Integrated Oiler	«Tool-Box «Bunded bottom box			

Dimensions



CERTIFICATION

GCCA:GC009G01
CE certification: Machinery Directive 2006/42/EC
GB/T 45001-2020/ISO 45001:2018 ,GB/T 24001-2016/ISO14001:2015, ISO9001:2015

WARRANTY COVERAGE

- PACKAGE:** 1 year or 2,000 hours
ENGINE: Carries the manufacturer's warranty
AIREND: STANDARD: 2 years or 4,000 hours
EXTENDED: 5 years or 10,000 hours with the use of GTL filters and fluids



XIAMEN GTL POWER SYSTEM CO.,LTD

Marketing Center: 5F, Bo an Shi Tong Building, No.997-999, Tianma Rd, Jimei,Xiamen,361100 **TEL:** +86 (0592)7196398

China Manufacturer Center :1#Factory Building No.8 Tonghong Rd, Tong'an District,Xiamen,361100,China **WEB:** www.cngtl.com

Effective Date: 01012025. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed are trademarks, service marks or trade-names of Xiamen GTL Power System Co.,Ltd

For more information, product demonstration, or details on purchase, lease and rental plans, please contact your local GTL distributor.